



ENDURO 816

- Comfort
- Touring
- Fuel Efficiency

Features & Benefits

- Equal Force Casing Construction - Allows for a more comfortable ride and better steering response

- Four Wide Longitudinal Grooves - Evacuate water efficiently for improved wet performance
- Silica Compound Design - Reduces rolling resistance, while providing exceptional grip in wet and dry road conditions
- Full nylon jointless cap ply - Improves uniformity and tire stability

Primewell offers the ENDURO 816 in 7 different tire sizes.

Tire Size	LI	SI	ETRTO	Standard RIM	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Max Load(kg)
225/60R16	98	H	6.5	6.0 - 7.0	225	676	8.1	750
235/60R16	100	H	7.0	6.5 - 8.5	235	688	8.2	800
225/65R17	102	H	6.5	6.0 - 8.0	225	724	8.1	850
P235/65R17	103	T	7.0	6.5 - 8.5	235	738	8.2	875
P225/60R17	98	T	6.5	6.0 - 8.0	225	702	8.1	750
235/60R17	102	T	7.0	6.5 - 8.5	235	714	8.2	850
P235/60R18	102	H	7.0	6.5 - 8.5	235	739	8.1	850