



ENDURO HT2

- Highway Terrain
- All Season

Features & Benefits

- New Tread Compound - Designed for improved mileage, grip, and durability
- Optimized Casing Tension Technology - Excellent balance of wet and dry handling
- Superior Tread Pattern Design - Excellent handling and ride comfort
- Advanced Noise- Canceling Tread Block Layout - Reduces road noise even at higher speeds

Primewell offers the ENDURO HT2 in 15 different tire sizes.

Tire Size	LI	SI	ETRTO	Standard RIM	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Max Load(kg)
LT235/85R16	120/11	R	6.5	6.0 - 7.5	235	806	10.2	1380/1260
	6							
LT225/75R16	115/11	R	6.0	6.0 - 7.5	225	744	10.2	1215/1120
	2							

P245/75R16	109	T	7.0	6.5 - 8.0	245	774	8.2	1030
P265/75R16	114	T	7.5	7.0 - 9.0	265	804	8.2	1180
P215/70R16	99	T	6.5	5.5 - 7.0	215	708	8.2	775
P225/70R16	101	T	6.5	6.0 - 7.5	225	722	8.2	825
P235/70R16	104	T	7.0	6.0 - 8.0	235	736	8.2	900
P245/70R16	106	T	7.0	6.5 - 8.0	245	750	8.2	950
P265/70R16	111	T	8.0	7.0 - 9.0	265	778	8.2	1090
P265/70R17	113	T	8.0	7.0 - 9.0	265	804	8.2	1150
P235/65R17	103	T	7.0	6.5 - 8.5	235	738	8.2	875
P245/65R17	105	T	7.0	7.0 - 8.5	245	750	8.2	925
P265/65R17	110	T	8.0	7.5 - 9.5	265	776	8.2	1060
P245/60R18	104	T	7.0	7.0 - 8.5	245	751	8.2	900
P265/60R18	109	T	8.0	7.5 - 9.5	265	775	8.2	1030